

Sizes 2" – 16"



The advantages of bolted sleeve couplings over other pipe repair processes

- No special pipe end required
 - Multiple types of pipe and pipe materials can be joined
 - Allows for limited expansion and contraction
 - Dampens vibration
 - Can be installed in any type of environment
 - No fire hazards because welding is not required—only the use of a wrench
 - Increases hoop strength of the pipe at the joint
-

Bolted Sleeve Couplings

Nominal Size (In)	Pipe O.D. (In)	Sleeve Length	Description	Style	Part #	Weight (Lbs)	Sleeve Thickness (In)	Bolted Data	
								Size	Quantity Required
2"	2 3/8"	5	2 × 5	380	S260148	8 3/4	5/32	5/8 × 8	3
		7	2 × 7	380	S260168	10	5/32	5/8 × 10	3
		12	2 × 12	400	S262529	12 1/2	5/32	5/8 × 15	3
		16	2 × 16	400	S262539	14	5/32	5/8 × 19	3
		24	3 × 24	400	S262549	20	5/32	5/8 × 27	3
2 1/2"	2 7/8"	5	2.5 × 5	380	S260193	10	3/16	5/8 × 8	3
		7	2.5 × 7	380	S260198	12	3/16	5/8 × 10	3
		12	2.5 × 12	400	S262574	15 1/2	3/16	5/8 × 15	3
		16	2.5 × 16	400	S262586	16	3/16	5/8 × 19	3
		24	2.5 × 24	400	S262599	19	3/16	5/8 × 27	3
3"	3 1/2"	5	3 × 5	380	S260218	12	5/32	5/8 × 8	4
		7	3 × 7	380	S260238	13 1/2	5/32	5/8 × 10	4
		12	3 × 12	400	S262624	17 1/2	5/32	5/8 × 15	4
		16	3 × 16	400	S262634	21	5/32	5/8 × 19	4
		24	3 × 24	400	S262644	23	5/32	5/8 × 27	4
4"	4 1/2"	5	4 × 5	380	S260288	13 3/4	5/32	5/8 × 8	4
		7	4 × 7	380	S260308	15 1/4	5/32	5/8 × 10	4
		12	4 × 12	400	S262714	20	5/32	5/8 × 15	4
		16	4 × 16	400	S262724	23	5/32	5/8 × 19	4
		24	4 × 24	400	S262734	32 1/2	5/32	5/8 × 27	4
5"	5 9/16"	5	5 × 5	380	S260505	21	9/32	5/8 × 8	6
		7	5 × 7	380	S260507	23 3/4	9/32	5/8 × 10	6
		12	5 × 12	400	S260512	27 3/4	9/32	5/8 × 15	6
		16	5 × 16	400	S260516	30 1/2	9/32	5/8 × 19	6
		24	5 × 24	400	S260524	46	9/32	5/8 × 27	6
6"	6 5/8"	5	6 × 5	380	S260423	22 1/2	1/4	5/8 × 8	6
		7	6 × 7	380	S260443	26 1/2	1/4	5/8 × 10	6
		12	6 × 12	400	S262720	34	1/4	5/8 × 15	6
		16	6 × 16	400	S262871	41	1/4	5/8 × 19	6
		24	6 × 24	400	S262872	59 1/2	1/4	5/8 × 27	6
8"	8 5/8"	5	8 × 5	380	S260513	27	7/32	5/8 × 8	6
		7	8 × 7	380	S260533	32	7/32	5/8 × 10	6
		12	8 × 12	400	S262755	37	7/32	5/8 × 15	6
		16	8 × 16	400	S262941	52 1/2	7/32	5/8 × 19	6
		24	8 × 24	400	S262961	69 1/2	7/32	5/8 × 27	6
10"	10 3/4"	5	10 × 5	380	S260558	32 1/2	7/32	5/8 × 8	8
		7	10 × 7	380	S260623	37 1/2	7/32	5/8 × 10	8
		12	10 × 12	400	S262800	55	7/32	5/8 × 15	8
		16	10 × 16	400	S262986	61 1/2	7/32	5/8 × 19	8
		24	10 × 24	400	S263006	84 1/2	7/32	5/8 × 27	8
12"	12 3/4"	5	12 × 5	380	S260603	39	1/4	5/8 × 8	8
		7	12 × 7	380	S260623	46 1/2	1/4	5/8 × 10	8
		12	12 × 12	400	S260805	59	1/4	5/8 × 15	8
		16	12 × 16	400	S263031	71	1/4	5/8 × 19	8
		24	12 × 24	400	S263051	95	1/4	5/8 × 27	8
14"	15 1/4"	16	14 × 16	400	S14X16400	130	1 1/4	5/8 × 19	8
16"	17 1/4"	16	16 × 16	400	S16X16400	154	1 1/4	5/8 × 19	8
		24	16 × 24	400	S16X24400	204	1 1/4	5/8 × 27	8