

Type 'D' / Model 7 / Pressure Gauge

Heavy Duty

7 7/8" Diameter



14 3/4"

- gauge provides quick, accurate pressure changes and minimizes fluctuations by having a built-in dampening mechanism. The gauge is ideal for reciprocating pumps.
- Temperature range: -50°F to 180°F
Liquid surrounding gauge mechanism minimizes wear from vibration and mechanical shock.
- Heavy duty seals create water-tight barrier around gauge mechanism.
- Impact resistant Amber lens are installed by O'Drill for easy reading from a distance of 20 to 30 feet.
- Connects with threaded female 2" line pipe.
- Type 'D' gauge is 14 3/4" high and 7 7/8" wide and comes with a 5" dial for easy reading.

To place an order, please specify:

- 1 Unit of measure and pressure range
- 2 Type of service
- 3 O'Drill part number

Part Numbers

Pressure Range	Standard Service	Salt Water Service	Corrosive Fluid Service
1,000 psi	PGD1M	PGD1MB	PGD1MS
3,000 psi	PGD3M	PGD3MB	PGD3MS
5,000 psi	PGD5M	PGD5MB	PGD5MS
6,000 psi	PGD6M	PGD6MB	PGD6MS
7,000 kPa	PGD7K	PGD7KB	PGD7KS
21,000 kPa	PGD21K	PGD21KB	PGD21KS
35,000 kPa	PGD35K	PGD35KB	PGD35KS
42,000 kPa	PGD42K	PGD42KB	PGD42KS
70 Bar	PGD7B	PGD7BB	PGD7BS
210 Bar	PGD21B	PGD21BB	PGD21BS
350 Bar	PGD35B	PGD35BB	PGD35BS
420 Bar	PGD42B	PGD42BB	PGD42BS

Note: Also available in kg/cm²

★ **Certification:**

All O'Drill - MCM Gauges come with full certification orders upon customer request

★ **Calibration:**

All gauges are calibrated to within 1% tolerance.

★ **Gauge Rebuilding Service**

O'Drill - MCM, Inc. can rebuild damaged or worn gauges to like new condition for a nominal cost.

★ **Ask us about Spare Parts!**

100% interchangeable with Oteco® & Cameron®

*Top Quality...
... Lowest Prices!*

- Shipping Weights:
- Standard Service 26 lbs. (11.9 kg)
 - Salt water service 35 lbs. (16 kg)
 - Corrosive service 26 lbs. (11.9 kg)